

# NEW!

## 75H WASTE OIL HEATER



### SPECIFICATIONS

<b>Fuel Flow Rate</b>	0.54 gallon/hour (2.0 L/hour)
<b>BTU</b>	75,000 BTU / hour (21.98 kW/hour)
<b>Heat Rise over Input Air</b>	100° F (250° F max outlet temp)
<b>Air Flow</b>	500 CFM
<b>Warm Outlet Dimensions</b>	10" x 12.5" (no ductwork allowed)
<b>Exhaust Flue Diameter</b>	6" (15cm)
<b>Unit Dimensions</b>	75" H x 21" W x 26" L
<b>Unit Weight</b>	210 lbs
<b>Tank Storage</b>	10 gallons
<b>Shipping Dimensions</b>	84" H x 36" W x 36" W
<b>Shipping Weight</b>	320 lbs
<b>Approved Fuels</b>	Used crankcase oils, ATF, No. 2 fuel oil
<b>Electrical Requirements</b>	115 VAC 60Hz, 8 amps. Connect to 10 amp circuit breaker (15 amp max)
<b>Regulation and Certification</b>	UL Listed - U.S. and Canada
<b>Warranty</b>	1 year or 1500 hours*
<b>Area Coverage</b>	Heats up to 1750 sq. ft.
<b>Mounting</b>	Bolts to non-combustible flooring
<b>Flue</b>	Exhaust through 6-Inch, Class A flue

### Included with Unit

Tee and draft control damper, air compressor, metering pump, draft manometer, hour meter, tank gauge, low fuel cutoff with indicator light, programmable thermostat, cleanable oil strainer in fill port and on pickup tube, flue kit

\*A second year will be activated when the product is registered with the manufacturer within the first 30 days of receipt of the product.



For more information call (800) 311-8828  
or visit [energyLogic.com](http://energyLogic.com)

